

CONTENTS

Introduction	3
General description	7
Features and benefits of Rulmeca Motorized Pulleys	9
<hr/>	
MOTORIZED PULLEY	12
Motorized Pulley 138LS	14
Motorized Pulley 165LS	20
Motorized Pulley 220M & 220H	26
Motorized Pulley 320L, 320M & 320H	32
Motorized Pulley 400M & 400H	40
Motorized Pulley 500H	46
Motorized Pulley 630M & 630H	50
Motorized Pulley 800M, H & 800HD	55
Motorized Pulley 1000H & 1000HD	60
Information needed when ordering	64
<hr/>	
PLANNING SECTION	66
Applications in special environmental conditions	68
Application worksheet - Bulk materials handling	70
Technical precautions for design, installation and maintenance	71
Oil contents in liter for standard	85
Oil contents in liter (l) for special constructions	86
Connection diagrams	87
Rulmeca and partner contacts	90



Production location of RULMECA Germany in the Center of Germany.



GENERAL DESCRIPTION

The Rulmeca Motorized Pulley was first produced in 1953 specifically for use on conveyors belt applications.

The aim was to produce a compact, hermetically sealed, highly efficient conveyor drive unit that would be unaffected by dust, water, oil, grease or other harmful substances. A Motorized Pulley that would be quick and simple to install and require virtually no maintenance.

These aims were achieved and today the Rulmeca Motorized Pulley is considered to be one of the most reliable, effective and safe conveyor drive systems available throughout the world.

The Rulmeca Motorized Pulley is a highly efficient geared motor drive, which is hermetically sealed in a steel cylindrical shell.

The shell, which is normally crowned to ensure belt tracking, is fitted with bearing housings incorporating precision bearings, double lipped oils seals and rotates on a pair of shafts.

The motor stator is fixed to the shafts and the motor winding cables passes through one of the shafts, eliminating the need for slip rings and brushes.

The squirrel cage induction motor, manufactured in steel laminate, is machined concentric to high tolerances and designed to give a strong starting torque for 3 phase versions.

The rotor pinion is coupled directly to the gearbox.

The gearbox transmits torque to the shell through a geared rim and provides a highly efficient motor, with very little frictional losses.

The Motorized Pulley is oil filled, which acts as a lubricant and coolant. Heat is dissipated through the shell and conveyor belt.

All components are manufactured using the latest technology.

Motorized Pulleys are produced according to following standards:

DIN VDE 0100

Group 400 "Protective measures"

VDE 0298

Application of cables and cords in power installations

VDE 0530

Rotating electrical machines (part of IEC 60034)

Directive 2014/30/EU

EMC - Electromagnetic compatibility

VDE 0839-6-4:2011-09

EMC- Electromagnetic compatibility-
Emmision standard for industrial environments

VDE 0838-3:2014-03

EMC- Electromagnetic compatibility-
Limitation of voltage changes, voltage fluctuations and flicker...

CE-Declaration:

CE-Declaration label on Motorized Pulley is valid for product conformity to Directive 2014/30/EU (EMC) and to Directive 2014/35/EU (low voltage limits)

Rulmeca Motorized Pulleys are manufactured according to the Council Directives of the European Communities.



Sea-dredged aggregates working in wet, salty and aggressive environment! IP66/67 sealing – a MUST – often with re-greasable seals!



Recycling application benefiting from IP66/67 sealing systems avoiding internal damage from aggressive ambient environments containing air or gas of high PH-values.